

Kieselit-Grundierfarbe

Version	Revision Date:	Print Date	Date of last issue: -
1.0	20.02.2019	08.04.2019	Date of first issue: 20.02.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier Trade name	:	Kieselit-Grundierfarbe
1.2 Relevant identified uses of t	the s	substance or mixture and uses advised against
Use of the Sub- stance/Mixture	:	Water-borne coatings
Recommended restrictions on use	:	within adequate application - none
1.3 Details of the supplier of the	e sat	fety data sheet
Company	:	Alligator Farbwerke GmbH Markstraße 203 32130 Enger
Telephone	:	+4952249300
Telefax		+4952247881
E-mail address Responsi- ble/issuing person	:	produktsicherheit@alligator.de
1.4 Emergency telephone numb	oer	
Emergency telephone num-	:	
ber 1		(Mon - Fri 08:00 - 16:00)
SECTION 2: Hazards identifi	cati	on
2.1 Classification of the substa	nce	or mixture
Classification (REGULATIC Not a hazardous substance of	•	
2.2 Label elements		
Labelling (REGULATION (E	EC) N	No 1272/2008)

Not a hazardous substance or mixture.

Precautionary statements	:	P101 If medical advice is needed, have product container or
		label at hand.
		P102 Keep out of reach of children.

according to Regulation (EC) No. 1907/2006

Kieselit-Grundierfarbe

Version	Revision Date:	Print Date	Date of last issue: -
1.0	20.02.2019	08.04.2019	Date of first issue: 20.02.2019

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Due to its potassium silicate content, the reaction of silicate based coatings is highly alkaline. Hence protect skin and eyes from paint.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature

: primer based on silicate, aqueous

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Silicic acid, potassium salt	1312-76-1 215-199-1 01-2119456888-17	Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335	>= 1 - < 10
Substances with a workplace expo	sure limit :	·	
Limestone	1317-65-3 215-279-6		>= 50 - < 70
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17		>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	:	First aider needs to protect himself. Move out of dangerous area. If you feel unwell, seek medical advice (show the label where possible). Never give anything by mouth to an unconscious person.
If inhaled	:	Move to fresh air.
In case of skin contact	:	In case of contact, immediately flush skin with soap and plenty of water. Do NOT use solvents or thinners. Take off all contaminated clothing immediately.
In case of eye contact	:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.
If swallowed	:	If swallowed, DO NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Seek medical advice.

according to Regulation (EC) No. 1907/2006

Kieselit	Kieselit-Grundierfarbe					
Version 1.0	Revision Date: 20.02.2019		int Date .04.2019	Date of last issue: - Date of first issue: 20.02.2019		
	4.2 Most important symptoms and effects, both acute and delayed None known.					
4.3 Indicati	ion of any immediate	me	dical attention and	d special treatment needed		
Treatm	-	:	No information av	-		
SECTION	5: Firefighting mea	sur	es			
5.1 Extingu	uishing media					
Suitable extinguishing media :		:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. Use water spray, alcohol-resistant foam, dry chemical or car- bon dioxide.			
Unsuitable extinguishing : media		:	None known.			
5.2 Special	I hazards arising from	the	e substance or mi	xture		
Specific hazards during fire- : fighting		In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocar- bons (smoke).				
5.3 Advice	for firefighters					
	Special protective equipment : Wear self-contained breathing apparatus for firefighting essary.		ned breathing apparatus for firefighting if nec-			
Further information : The product itself does not burn. Standard procedure for chemical fires. Use water spray to cool unopened containers.			ure for chemical fires.			

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures					
Personal precautions :	Do not get in eyes, on skin, or on clothing. Material can create slippery conditions. Use protective shoes or boots with rough rubber sole.				
6.2 Environmental precautions					
Environmental precautions :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Prevent further leakage or spillage if safe to do so.				
6.3 Methods and material for contai	nment and cleaning up				

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel,
		acid binder, universal binder, sawdust).
		Keep in suitable, closed containers for disposal.

according to Regulation (EC) No. 1907/2006

Kieselit-Grundierfarbe

Version	Revision Date:	Print Date	Date of last issue: -
1.0	20.02.2019	08.04.2019	Date of first issue: 20.02.2019

6.4 Reference to other sections

For disposal considerations see section 13., For personal protection see section 8., For further information see Section 7 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling	3	
Advice on safe handling	:	No special technical protective measures required. For personal protection see section 8.
Hygiene measures	:	Do not eat, drink or smoke when using this product. Wash hands before eating, drinking, or smoking.
7.2 Conditions for safe storage, i	ncl	uding any incompatibilities
Requirements for storage areas and containers	:	Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store at room temperature in the original container. To maintain product quality, do not store in heat or direct sunlight. Perishable if frozen.
Advice on common storage	:	Keep away from oxidizing agents and strongly acid or alkaline materials.
7.3 Specific end use(s)		

Specific use(s) : Please follow the technical information.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
Limestone	1317-65-3	TWA (inhalable	10 mg/m3	GB EH40
		dust)		
Further information	fractions of air in accordance sampling and COSHH defin kind when pre 8-hour TWA of This means th above these lo posure to these contain particul of any particul body response HSE distinguis ble' and 'respi	borne dust which wi with the methods de gravimetric analysis ition of a substance sent at a concentrat of inhalable dust or 4 hat any dust will be s evels. Some dusts has evels. Some dusts has evels of a wide range of lar particle after entry e that it elicits, dependent shes two size fractio rable'., Inhalable dust	espirable dust and inhalable Il be collected when sampling escribed in MDHS14/3 Gene of respirable and inhalable of hazardous to health includes ion in air equal to or greater mg.m-3 8-hour TWA of resp ubject to COSHH if people a ave been assigned specific V the appropriate limit., Most in f sizes. The behaviour, depory y into the human respiratory nd on the nature and size of ns for limit-setting purposes at approximates to the fraction mouth during breathing and i	g is undertaken ral methods for dust, The dust of any than 10 mg.m-3 irable dust. re exposed VELs and ex- ndustrial dusts sition and fate system and the the particle. termed 'inhala- n of airborne

according to Regulation (EC) No. 1907/2006

Kieselit-Grundierfarbe

available for deposition in the respiratory tract. Respirable dust approximate to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDFS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limit should be complied with., Where no specific short-term exposure init is list a figure three times the long-term exposure should be used TWA (Respirable dust) I way (Respirable dust) I way (Respirable dust) BEH40 Further information For the purposes of these limits, respirable dust and inhalable dust are thos fractions of airborne dust which will be collected when sampling is undertak in accordance with the methods described in MDFS1412 General methods f sampling and gravimetric analysis of respirable and inhalable dust of any kind when present at a concentration in air equal to or greater than 10 mg m 8-hour TWA of inhalable dust or 4 mg.m. 3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and ex- posure to these must comply with the appropriate limit, Nost industrial dust contain particles of a wide range of sizes. The behaviour, deposition and fat of any particular particle after entry into the human respiratory system and I body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable be' and 'respirable', inhalable dust approximates to the fraction of airborne material that enters the nose and mount duning breathing and is therefore available for deposition in the respirabry tract. Respirable dust approximate be' and 'respirable', unhalable dust are thos fractions of airborne dust whind will be collected when samgling is undertakk in	ersion)	Revision Dat 20.02.2019			ate of last issue: - ate of first issue: 20.02.2019	
to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limit is build be compiled with., Where no specific short-term exposure limits is its a figure three times the long-term exposure should be used TWA (Respirable 4 mg/m3 GB EH40 Just GB EH40 GB EH40 Further information For the purposes of these limits, respirable dust and inhalable dust are thos fractions of airborne dust which will be collected when sampling is undertakk in accordance with the methods described in MDHS14/3 General methods of sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg. The above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit. Most industrial dust contain particular particule after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable dust approximates to the fraction of a substance hazardous beside. Just Halable dust approximates to the fraction of a dust or the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3. Where dusts contain components that have their own assigned WEL, all the relevant limit should be complied with., Where no specific short-term exposure limit is list a figure three times the long-term exposure should be used						
Burther information For the purposes of these limits, respirable dust and inhalable dust are thos fractions of airborne dust which will be collected when sampling is undertake in accordance with the methods described in MDHS14/3 General methods f sampling and gravimetric analysis of respirable and inhalable dust. The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg. M B-hour TWA of inhalable dust or 4 mg. M - 8 whort TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit. Most industrial dust contain particles of a wide range of sizes. The behaviour, deposition and fat of any particular particle after entry into the human respiratory system and it body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable bie' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction of airborne dust approximates to the fraction of airborne dust approximates to the garce entry into the fraction sint where the system entry material are given in MDHS14/3. Where dusts contain components that have their own assigned WEL, all the relevant limit should be complied with., Where no specific short-term exposure limit is list a figure three times the long-term exposure should be used tittanium dioxide 13463-67-7 TWA (inhalable 10 mg/m3 GB EH40 COSHH definition of a substance hazardous to health includes dust of any kind			to the fraction definitions and contain compo- should be con	that penetrates to the d explanatory mater onents that have the oplied with., Where	ne gas exchange region of the al are given in MDHS14/3., v ir own assigned WEL, all the no specific short-term expos	ne lung. Fuller Where dusts e relevant limit
Further information For the purposes of these limits, respirable dust and inhalable dust are thos fractions of airborne dust which will be collected when sampling is undertakk in accordance with the methods described in MDHS14/3 General methods f sampling and gravimetric analysis of respirable and inhalable dust. The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and ex- posure to these must comply with the appropriate limit, Most industrial dust contain particles of a wide range of sizes. The behaviour, deposition and fat of any particular particle after entry into the human respiratory system and ti body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable ble' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mound during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximit should be complied with., Where no specific short-term exposure about approximit is list a figure three times the long-term exposure should be used titanium dioxide 13463-67-7 TWA (inhalable 10 mg/m3 GB EH40 GB EH40 dust) Further information For the purposes of these limits, respirable dust and inhalable dust of any kind when present at a concentration in air equal to or greater than 10 mg.m 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust in accordance with the methods described in MDHS14/3 Genereal methods f				· ·	4 mg/m3	GB EH40
fractions of airborne dust which will be collected when sampling is undertakk in accordance with the methods described in MDHS14/3 General methods f sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and ex- posure to these must comply with the appropriate limit., Most industrial dust contain particles of a wide range of sizes. The behaviour, deposition and fat of any particular particle after entry into the human respiratory system and tit body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalab ble' and 'respirable',Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximate to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3, Where dusts contain components that have their own assigned WEL, all the relevant limit should be complied with., Where no specific short-term exposure limit is list a figure three times the long-term exposure should be used tittanium dioxide 13463-67-7 TWA (inhalable dust) IO mg/m3 GB EH40 Further information For the purposes of these limits, respirable dust and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to grea					<u> </u>	
titanium dioxide13463-67-7TWA (inhalable dust)10 mg/m3GB EH40Further informationFor the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertake in accordance with the methods described in MDHS14/3 General methods f sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dust contain particles of a wide range of sizes. The behaviour, deposition and fat of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable ble' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximate to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limit should be complied with., Where no specific short-term exposure limit is lister			fractions of air in accordance sampling and COSHH defin kind when pre 8-hour TWA of This means th above these le posure to these contain particul body response HSE distinguis ble' and 'respi material that e available for d to the fraction definitions and contain compo- should be com	borne dust which we with the methods d gravimetric analysis ition of a substance sent at a concentration of inhalable dust or 4 hat any dust will be sevels. Some dusts has evels. Some dusts has evels. Some dusts has evels. Some dusts has evels a wide range of lar particle after entri- e that it elicits, dependent shes two size fraction rable'., Inhalable du enters the nose and leposition in the resp that penetrates to the d explanatory materi- onents that have the applied with., Where	ill be collected when samplir escribed in MDHS14/3 Gene of respirable and inhalable hazardous to health includes tion in air equal to or greater mg.m-3 8-hour TWA of resp subject to COSHH if people a ave been assigned specific the appropriate limit., Most of sizes. The behaviour, depoy y into the human respiratory nd on the nature and size of ons for limit-setting purposes st approximates to the fraction mouth during breathing and biratory tract. Respirable dus ne gas exchange region of the al are given in MDHS14/3., Ver own assigned WEL, all the no specific short-term expose	ig is undertake eral methods f dust, The s dust of any than 10 mg.m birable dust. are exposed WELs and ex- industrial dusts osition and fat system and th the particle. termed 'inhala on of airborne is therefore t approximate he lung. Fuller Where dusts e relevant limit
Further information For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaked in accordance with the methods described in MDHS14/3 General methods f sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dust contain particles of a wide range of sizes. The behaviour, deposition and fat of any particular particle after entry into the human respiratory system and th body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable for deposition in the respiratory tract. Respirable dust approximate to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximate to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limit should be complied with., Where no specific short-term exposure limit is listed or the fraction that penetrates to the inter own assigned wEL, all the relevant limit should be complied with., Where no specific short-term exposure limit is listed or the particle with, where no specific short-term exposure limit is listed or the particle with.	titaniu	ım dioxide		TWA (inhalable		GB EH40
fractions of airborne dust which will be collected when sampling is undertake in accordance with the methods described in MDHS14/3 General methods f sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m 8-hour TWA of inhalable dust or 4 mg.m-3 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and ex- posure to these must comply with the appropriate limit., Most industrial dust contain particles of a wide range of sizes. The behaviour, deposition and fat of any particular particle after entry into the human respiratory system and th body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhala ble' and 'respirable'., Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximate to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limit should be complied with., Where no specific short-term exposure limit is lister	Furth	er information	For the purpo		espirable dust and inhalable	dust are those
	T UI UI		fractions of ail in accordance	borne dust which w with the methods d	ill be collected when samplir	ng is undertake

according to Regulation (EC) No. 1907/2006

Kieselit-Grundierfarbe

Version	Revision Da 20.02.2019	te: Print Date	Date of last issue: -
1.0		08.04.2019	Date of first issue: 20.02.2019
Furth	er information	fractions of airborne dual in accordance with the sampling and gravimetr COSHH definition of a skind when present at a 8-hour TWA of inhalabl This means that any dual above these levels. Som posure to these must contain particles of a with of any particular particles body response that it el HSE distinguishes two ble' and 'respirable'., Init material that enters the available for deposition to the fraction that pener definitions and explanation contain components that should be complied with	se limits, respirable dust and inhalable dust are those st which will be collected when sampling is undertaken methods described in MDHS14/3 General methods for ic analysis of respirable and inhalable dust, The substance hazardous to health includes dust of any concentration in air equal to or greater than 10 mg.m-3 e dust or 4 mg.m-3 8-hour TWA of respirable dust. st will be subject to COSHH if people are exposed ne dusts have been assigned specific WELs and ex- omply with the appropriate limit., Most industrial dusts de range of sizes. The behaviour, deposition and fate e after entry into the human respiratory system and the icits, depend on the nature and size of the particle. size fractions for limit-setting purposes termed 'inhala- nalable dust approximates to the fraction of airborne nose and mouth during breathing and is therefore in the respiratory tract. Respirable dust approximates etrates to the gas exchange region of the lung. Fuller tory material are given in MDHS14/3., Where dusts at have their own assigned WEL, all the relevant limits n., Where no specific short-term exposure limit is listed, long-term exposure should be used

8.2 Exposure controls

Personal protective equipment

Eye protection	:	Safety glasses
Hand protection Material Glove thickness Protective index	:	Nitrile rubber 0,2 mm Class 3
Remarks	:	Wear suitable gloves tested to EN374. Before removing gloves clean them with soap and water.
Skin and body protection	:	Long sleeved clothing Safety shoes
		Choose body protection according to the amount and con- centration of the dangerous substance at the work place.
		Skin should be washed after contact.
Respiratory protection	:	During spray application: Do not breathe spray dust. Use A2/P2 combination filter for paint spraying.

according to Regulation (EC) No. 1907/2006

Kieselit-Grundierfarbe

Version	Revision Date:	Print Date	Date of last issue: -
1.0	20.02.2019	08.04.2019	Date of first issue: 20.02.2019

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	white
Odour	:	No data available
Odour Threshold	:	Not relevant
рН	:	< 11,4
Melting point/freezing point	:	not determined
Boiling point/boiling range	:	not determined
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	The product is not flammable.
Upper explosion limit / Upper flammability limit	:	not determined
Lower explosion limit / Lower flammability limit	:	not determined
Vapour pressure	:	not determined
Relative vapour density	:	not determined
Relative density	:	not determined
Density	:	1,6200 g/cm3
Solubility(ies) Water solubility	:	completely miscible
Partition coefficient: n- octanol/water	:	not determined
Auto-ignition temperature	:	not determined
Decomposition temperature	:	Not applicable
Viscosity Viscosity, dynamic	:	No data available
Explosive properties	:	Not applicable
Oxidizing properties	:	Not applicable

according to Regulation (EC) No. 1907/2006

Kieseli	t-Grundierfarb	е	
Version 1.0	Revision Date: 20.02.2019	Print Date 08.04.2019	Date of last issue: - Date of first issue: 20.02.2019
	information ata available		
SECTION	10: Stability and	reactivity	
10.1 Reac	tivity		
No de	ecomposition if stored	and applied as dire	cted.
10.2 Chen	nical stability		
No de	ecomposition if stored	and applied as dire	cted.
10.3 Poss	ibility of hazardous	reactions	
Haza	rdous reactions	: No decomp	osition if stored and applied as directed.
10.4 Conc	litions to avoid		
Cond	itions to avoid	: Protect fron	n frost, heat and sunlight.
10.5 Incor	npatible materials		
Mater	rials to avoid		e with oxidizing agents. e with acids and bases.
10.6 Haza	rdous decompositio	on products	
No de	ecomposition if stored	and applied as dire	cted.

11.1 Information on toxicological effects

Acute toxicity		
Product:		
Acute oral toxicity	:	Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	Based on available data, the classification criteria are not met.
Skin corrosion/irritation		
Product:		
Remarks	:	According to the classification criteria of the European Union, the product is not considered as being a skin irritant.
Components:		
Limestone:		
Remarks	:	According to the classification criteria of the European Union, the product is not considered as being a skin irritant.

according to Regulation (EC) No. 1907/2006

Kieselit-Grundierfarbe

rsion)	Revision Date: 20.02.2019	Print Date 08.04.2019	Date of last issue: - Date of first issue: 20.02.2019
Serio	us eye damage/eye	irritation	
Produ	uct:		
Rema	arks		to the classification criteria of the European Unit is not considered as being an eye irritant.
<u>Com</u>	oonents:		
Lime	stone:		
Rema	arks		to the classification criteria of the European Unit is not considered as being an eye irritant.
Resp	iratory or skin sensi	tisation	
Produ	uct:		
Rema	arks	: No data ava	ailable
<u>Com</u>	oonents:		
Lime	stone:		
Rema	arks	: No data ava	ailable
Furth	er information		
<u>Com</u>	oonents:		
Lime	stone:		
Rema	arks	: No data ava	ailable

SECTION 12: Ecological information

12.1 Toxicity

Product:		
Toxicity to fish	:	No data available
Toxicity to daphnia and other aquatic invertebrates	:	No data available
12.2 Persistence and degradabili No data available	ity	
12.3 Bioaccumulative potential		

No data available

12.4 Mobility in soil

No data available

according to Regulation (EC) No. 1907/2006

Kieselit-Grundierfarbe

Revision Date: 20.02.2019			Date of last issue: - Date of first issue: 20.02.2019	
s of PBT and vPvB a	asse	ssment		
<u>t:</u>				
Assessment		: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher		
dverse effects				
<u>t:</u>				
al ecological infor-	:		al hazard cannot be excluded in the event of andling or disposal.	
	20.02.2019 s of PBT and vPvB a	20.02.2019 08 s of PBT and vPvB asse <u>t:</u> ment : dverse effects <u>t:</u>	20.02.2019 08.04.2019 s of PBT and vPvB assessment t: ment : This substance/r to be either pers very persistent a 0.1% or higher dverse effects t: hal ecological infor- : An environmental	

SECTION 13: Disposal considerations

13.1 Waste treatment methods		
Product	:	Materials and all related packaging must be disposed of in a safe way in accordance with the full requirements of the local, regional, national and international authorities.
		Waste should not be disposed of via wastewater.
Contaminated packaging	:	Only completely emptied containers should be given for recy- cling.
Waste Code	:	used product 080112, waste paint and varnish other than those mentioned in 08 01 11*

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks

: Not classified as dangerous in the meaning of transport regulations. see sections 6-8

according to Regulation (EC) No. 1907/2006

Kieselit-Grundierfarbe

Version	Revision Date:	Print Date	Date of last issue: -
1.0	20.02.2019	08.04.2019	Date of first issue: 20.02.2019

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	This product is a mixture and does not contain Substances of Very High Concern (SVHC) equal or above 0.1%. Therefore no advised uses have to be defined and no chemical safety assessment has to be gener- ated.
REACH - List of substances subject to authorisation (Annex XIV)	:	None

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. Not applicable

Volatile organic compounds	: Directive 2004/42/EC
	< 0.1 %
	< 1 g/l

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance.

SECTION 16: Other information

Full text of H-Statements				
H315	:	Causes skin irritation.		
H319	:	Causes serious eye irritation.		
H335	:	May cause respiratory irritation.		
Full text of other abbreviations				
Eye Irrit.	:	Eye irritation		
Skin Irrit.	:	Skin irritation		
STOT SE	:	Specific target organ toxicity - single exposure		
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits		
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)		

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw -Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELX - Loading rate associated with x% response; EMS - Emergency Schedule; ENCS -Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP -Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IEC - International Covin Practice; IARC - International Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - Lethal Dose to 50% of a test population for Standardization; KECI - Korea Existing Chemicals Inventory; LCSO - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELF - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; SUECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety

according to Regulation (EC) No. 1907/2006

Kieselit-Grundierfarbe

Version	Revision Date:	Print Date	Date of last issue: -
1.0	20.02.2019	08.04.2019	Date of first issue: 20.02.2019

TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

REACH Information

According to our legal obligation we implement the Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH). We will adjust and update our safety data sheets on a regular base in accordance with the information of our upstream-suppliers. As usual we will inform you about the adjustments.

Regarding to the REACH regulation we would like to point out that DAW as a downstream user will not register on behalf of our company. We will rely on information from our suppliers. As soon as new information is available our safety data sheets will be amended accordingly. This will be put into practice depending on the register-deadline of the substances involved during the transition period from December 1, 2010 till May 31, 2018.

GB / EN