


## Anschlussleiste PLUS

Connecting fabric profile as sealing profile with fabric stripe and integrated compressed joint sealing tape für connections to windows and doors.



### Product characteristics

<b>Properties</b>	<ul style="list-style-type: none"><li>• With integrated expandable joint sealing tape</li><li>• Non-ageing</li><li>• Weatherproof</li><li>• Firmly connected fabric stripe</li><li>• High adhesive strength</li><li>• Limiting border (gauge) for the application of reinforcement compounds</li><li>• Self-adhesive flap for fastening of cover sheets</li><li>• Creates uniform joints (no cut, no permanently elastic sealing compound required)</li><li>• Fabric stripe based on Gittermatte (identical quality - no mismatch)</li><li>• UV-resistant</li><li>• Driving rain proof</li><li>• Can be processed with all reinforcement compounds of the ALLFAtherm thermal insulation systems</li></ul>
<b>Suitable substrates in detail</b>	<ul style="list-style-type: none"><li>• In all ALLFAtherm insulation systems.</li><li>• Recommended for window constructions up to 10 m<sup>2</sup> and insulation thicknesses up to 300 mm.</li><li>• Suitable for windows mounted in soffit level, flush to the façade and in insulation plane level.</li><li>• Serves as formation and sealing of connections between ALLFAtherm insulation systems and adjacent building parts.</li></ul>

### Material description

<b>Material base</b>	Synthetic and glass fabric
<b>Average consumption (short text)</b>	1 m/m
<b>Colour shade</b>	Profile body: white Mesh: green
<b>Storage</b>	Store evenly and dry

### Substrates

<b>Suitable substrates</b>	For door and window frames of plastics, aluminium or wood with solid and supporting coatings
<b>Substrate conditions</b>	The substrate must be clean, even, dry, sound and firm, free from parting agents, stable and suitable for adhesion. Produce an adhesion sample on the original substrate, with the profile. Hint: In order to ensure a safe installation, windows and doors have to be fixed in compliance with the applicable directives of the associations (such as RAL Gütegemeinschaft Fenster und Haustüren) and according to the state of the art, so as to exclude inadmissible motions.

## Anschlussleiste PLUS

### Application

#### Application

The connecting profile must be mounted prior to the installation of the insulation boards. Before fixing the profiles check the adhesion by trial. For this stick the profile to the window frame and press on. Remove with a jerk after about 10 minutes. If the foam sealing tape tears up and residues remain on the entire length on the window frames, the test has been passed and the profile can be mounted. Use a specific cleaner to remove all residues. Avoid the formation of butt joints, this means that entire lengths are to be used or lengths have to be adapted to the present situation. If necessary form butt joints on vertical connections in the upper third in order to keep the moisture load low. All works on the profiles (cut to length, mitre etc.) must be finished before the adhesion. First of all align the entire profile and press on slightly. After the right placing press firmly on over the entire profile length. A high contact pressure is crucial for the adhesive strength and thus for the final adhesion. The reinforcement mesh of the subsequent reinforcement surface must join the plaster. The plaster system must not exceed the predetermined breaking point of the plastic web to be removed by bending, as otherwise the web cannot be removed properly.

#### Application hints

The following regulations have to be observed and to be complied with during the application: ALLIGATOR application guidelines, the relevant valid building approvals, the current ALLFAtherm application brochure and in Germany BFS Fact Sheet No. 21, DIN 55699 as well as Technical System Information "Compendium ETICS and Fire Protection" published by the professional association Wäremedämmverbundsysteme (ETICS).

### Information

#### Waste disposal

Product residues can be disposed of as construction site waste.

### Container size

#### Content

25 Stück

2,5 m

#### EAN code

4002822021825

#### Article no.

869829

This data sheet cannot deal with all types of application arising in practice. Therefore, we cannot be held responsible for their content. These instructions do not release the purchaser / applicator from his responsibility of professionally examining the substrate and determining the suitability of the product in consideration of the project characteristics. In case of queries please request the technical assistance of ALLIGATOR FARBWERKE.